Amendments to the Claims:

Claims 2 to 10 are amended and claim 11 is added as set forth hereinafter.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Previously Presented) A hydro bushing for radially supporting a motor, the hydro bushing comprising:

a sleeve-shaped outer body;

an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between said outer body and said support body;

a volume-changeable work chamber disposed between said legs of said spring body and filled with a low-viscous hydraulic fluid;

said volume-changeable work chamber having a clear distance between said inner support body and said sleeve-shaped outer body;

at least one compensating chamber disposed laterally of and directly next to said work chamber;

said compensation chamber and said work chamber having a common lateral surface therebetween;

a transfer channel interconnecting said work chamber and said compensating chamber and being delimited by said common

lateral surface;

said work chamber having an effective cross-sectional area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a cross-sectional area (A_2); and,

said cross-sectional area (A_1), said dynamic swell stiffness, said length (L) and said cross-sectional area (A_2) all being so selected that said hydro bushing has a natural or resonant frequency of approximately 130 Hz.

2. (Currently Amended) ~~The hydro bushing of claim 1, wherein~~ A hydro bushing for radially supporting a motor, the hydro bushing comprising:

a sleeve-shaped outer body;

an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between said outer body and said support body;

a volume-changeable work chamber disposed between said legs of said spring body and filled with a low-viscous hydraulic fluid;

said volume-changeable work chamber having a clear distance between said inner support body and said sleeve-shaped outer body;

at least one compensating chamber disposed laterally of and directly next to said work chamber;

said compensation chamber and said work chamber having a common lateral surface therebetween;

a transfer channel interconnecting said work chamber and

said compensating chamber and being delimited by said common lateral surface;

said work chamber having an effective cross-sectional area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a cross-sectional area (A_2);

said cross-sectional area (A_1), said dynamic swell stiffness, said length (L) and said cross-sectional area (A_2) all being so selected that said hydro bushing has a natural or resonant frequency of approximately 130 Hz;

said transfer channel [[is]] being a first transfer channel;

said compensating chamber [[is]] being a first compensating chamber on one side of said work chamber; ~~chamber and said hydro bushing further comprises~~

a second compensating chamber on the other side of said work chamber;

a connecting channel connecting said compensating channels to each other; and,

a second transfer channel interconnecting said work chamber and said second compensating chamber.

3. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio of the effective cross-sectional area (A_1) of said work chamber to the cross-sectional area (A_2) of said transfer channel lies in a range of 0.1 to 10.

4. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio (A_1:A_2) of said cross-sectional areas (A_1

and A_2) is approximately 2.2.

5. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio of said length (L) of said transfer channel to said cross-sectional area (A_2) of said transfer channel lies in a range of 0.1 to 4.0.

6. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio of said length (L) of said transfer channel to said cross-sectional area (A_2) of said transfer channel is approximately 1.5.

7. (Currently Amended) ~~The hydro bushing of claim 1, wherein~~ A hydro bushing for radially supporting a motor, the hydro bushing comprising:

a sleeve-shaped outer body;

an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between said outer body and said support body;

a volume-changeable work chamber disposed between said legs of said spring body and filled with a low-viscous hydraulic fluid;

said volume-changeable work chamber having a clear distance between said inner support body and said sleeve-shaped outer body;

at least one compensating chamber disposed laterally of and directly next to said work chamber;

said compensation chamber and said work chamber having a

common lateral surface therebetween;

a transfer channel interconnecting said work chamber and said compensating chamber and being delimited by said common lateral surface;

said work chamber having an effective cross-sectional area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a cross-sectional area (A_2);

said cross-sectional area (A_1), said dynamic swell stiffness, said length (L) and said cross-sectional area (A_2) all being so selected that said hydro bushing has a natural or resonant frequency of approximately 130 Hz; and,

said cross-sectional area (A_1) of said work chamber ~~includes~~ including a constriction.

8. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the volume of said work chamber and the volume of said transfer channel define a ratio of 0.1 to 4.0.

9. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the volume ratio of said work chamber and said transfer channel is between 1.0 and 3.0.

10. (Currently Amended) ~~The hydro bushing of claim 1, wherein~~ A hydro bushing for radially supporting a motor, the hydro bushing comprising:

a sleeve-shaped outer body;

an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between said outer body and said support body;

a volume-changeable work chamber disposed between said legs of said spring body and filled with a low-viscous hydraulic fluid;

said volume-changeable work chamber having a clear distance between said inner support body and said sleeve-shaped outer body;

at least one compensating chamber disposed laterally of and directly next to said work chamber;

said compensation chamber and said work chamber having a common lateral surface therebetween;

a transfer channel interconnecting said work chamber and said compensating chamber and being delimited by said common lateral surface;

said work chamber having an effective cross-sectional area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a cross-sectional area (A_2);

said cross-sectional area (A_1), said dynamic swell stiffness, said length (L) and said cross-sectional area (A_2) all being so selected that said hydro bushing has a natural or resonant frequency of approximately 130 Hz; and,

one of said legs ~~separates~~ separating said work chamber from said compensation chamber and ~~ends~~ ending in spaced relationship to said sleeve-shaped outer body so as to define said common lateral surface.

11. The hydro bushing of claim 2, wherein said cross-sectional area (A_1) of said work chamber includes a constriction.